

TECHNICAL CHARACTERISTICS

SELENIA K

PRODUCT CODE: 1142

APPLICATION

Synthetic lubricant ideal for the most modern petrol engines. Owing to its unique formula, it warrants high resistance to oxidation, the utmost protection in "Stop & Go" driving and outstanding performance whatever the weather.

SPECIFICATIONS

SAE 5W-40, ACEA A3/B3, API SM, FIAT 9.55535-M2 CONTRACTUAL TECHNICAL REFERENCE N°F214.I05, VW 505.00, VW 502.00, MB-Approval 229.3

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
DENSITY 15°C	ASTM D 4052	g/cm ³	0,857
VISCOSITY @ 100°C	ASTM D 445	cSt	14,3
VISCOSITY INDEX	ASTM D 2270	--	170
FLASH POINT CI. O. C.	ASTM D 92	°C	232
T.B.N.	ASTM D 2896	mg KOH/g	10,2
POUR POINT	ASTM D 97	°C	<-33
FOAM @ 24°C	ASTM D 892	cc/s	TRACES/0

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

11/2010