

TECHNICAL CHARACTERISTICS

SELENIA WR 5W-40

PRODUCT CODE: 1092

APPLICATION

All-weather multiviscosity grade lubricant for latest generation Diesel engines. Guarantees excellent cold starting, lower consumption and maximum protection, even at low service temperatures.

SPECIFICATIONS

SAE 5W-40, ACEA B3/B4, API CF,
FIAT 9.55535-N2 CONTRACTUAL TECHNICAL REFERENCE N°F515.D06, MB-Approval 229.3, VW 505.00,
VW 502.00, GM-LL-B-025

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
DENSITY 15°C	ASTM D4052	g/cm ³	0,856
VISCOSITY @ 100°C	ASTM D445	cSt	15,0
VISCOSITY INDEX	ASTM D 2270	--	175
FLASH POINT CI. O. C.	ASTM D 92	°C	>200
T.B.N.	ASTM D 2896	mg KOH/g	10,2
POUR POINT	ASTM D 97	°C	<-36
FOAM @ 24°C	ASTM D 892	cc/s	TRACES/0

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

03/2014